

M5 CEILING FILTER ROLL



► TECHNICAL SPECIFICATIONS

Filter Media	Synthetic Fibre
Weight	500 - 600 g/m ²
Thickness	18 - 22 mm
Classification (EN779:2012)	M5
Flammability (DIN53438)	F1
Final Pressure Drop	250 Pa
Max. Temperature	90°C
Max. Humidity	100%



PRODUCT CODE	WIDTH (m)	LENGTH (m)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)	WEIGHT (Kg)
M5	2	20	40	4000	40	24
M5	1	20	20	2000	40	12

AC IMPREGNATED POLYESTER ROLL

► TECHNICAL SPECIFICATIONS



Filter Media	Activated Carbon Impregnated Polyester
Thickness	12 mm
Classification (EN779:2012)	G3
Classification (ISO 16890)	ePMcoarse %45
Flammability (DIN53438)	F1
Final Pressure Drop	250 Pa
Max. Temperature	90 °C
Max. Humidity	100%

PRODUCT CODE	WIDTH (m)	LENGTH (m)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10 % Pa)
AC	2	20	40	5400	40