

TWO BOLT THREAD FILTER CARTRIDGE



➤ Support Details

Top Cap	Bottom Cap	Inner Mesh	Gasket
Galvanized Steel or Molded polyurethane (PU) - soft. With 2 bolts	Galvanized Steel or Molded polyurethane (PU) - soft.	Galvanized Steel or Plastic ABS	EPDM or Silicone

➤ Filter Media Details

Media	Brand	Air Permeability (at 200 Pa)	Pore Size (μ)
Cellulose	Neenah Filtration (DE)	280 l/m2	45
Polyester	General Tekstil (TR)	85 l/m2	5
PTFE Coating Polyester	JP Air (DK)	370 l/m2	1,2
Alu Coating Polyester	JP Air (DK)	470 l/m2	1,2
Oleo/Hydrophobic Polyester	JP Air (DK)	470 l/m2	1
Flame Retardant Blend	Hifyber (TR)	170 l/m2	0,4

Suitable for:

- Cement
- Metals
- Food & Beverages
- Woodwork
- Powder Coating
- Sand Blasting
- Textile
- Chemicals
- Laser Cutting

<http://www.filtras.com.tr/>

Tuna Mh. 5601 Sk. No: 4-8 Bornova 35600 İzmir - Türkiye
+90 232 461 1118 - info@filtras.com.tr